

Special Feature

Comprehensive survey of useful lists and graphs for experiment

Complete power supply device note

Introduction 60	Engineer support project ... editorial mission part 2 : Design of high-performance power supply for eco-era !
Chapter 1 63	Semiconductor devices for on-board power supply Various high-efficiency power supplies for microcomputer board
Chapter 2 81	Electronic components for on-board power supply How to select key components [capacitors and inductors]
Chapter 3 86	Discreet/IC/module power supply device From control IC to power MOSFETs/diodes
Column A 88	Standard name list of discreet semiconductor package
Appendix 100	Circuit simulator for power electronics
Chapter 4 101	Electronic components/Mechanical components Electrolytic capacitor, fuse, rectifier diode, AC inlet socket
Chapter 5 112	Design and selection of transformer Ferrite core, bobbin, winding material
Chapter 6 121	Estimation of heat value and selection of heat radiator From internal temperature calculation of IC chip to radiation design
Column A 133	Q&A for heat calculation of linear regulators
Chapter 7 134	Print board design Estimation of inductance/resistor of print pattern
Column A 139	Impact of plating and temperature on resistance value of print pattern
Chapter 8 140	Noise suppression and safety regulation Countermeasure against switching noise

Device utilization

- 147** Ideal for power meter with simultaneous sampling of 7 channels
Ultra low consumption microcomputer with built-in seven 16bit ADC
-
- 153** External components are two capacitors and one coil
Low ripple DC-DC converter IC "XC9236/37" at 10mV_{P-P} with 92% efficiency
-
- 160** Check the improved points of PIC16F88 by experiment
Successor model of standard PIC "PIC16F1827"
-
- 168** Fabrication of digital scale to adjust A-D converted value with program
H8 microcomputer with built-in 14bit A-D converter "H8/38086R"
-
- 176** Experiment validation by using the switching power supply controller IC without photo coupler "LT3573"
Estimation of loop characteristic from output impedance which is getting difficult to measure due to ICs
-
- 222** Without additional power supply circuits
Prevent battery from damage by hyperelectric discharge

Serialization

- 185** Natural energy use in eco-era <5>
Water-wheel generator with LED message panel
-
- 191** Frame rate conversion technique using line memory built-in FPGA
Making of video converter from composite signal to analog RGB one
-
- 198** Introduction to digital filter without mathematical formula <9>
Converter with oversampling feature
-
- 207** Challenge to CMOS analog IC design <12>
Shape error of layout
-
- 214** CMOS analog circuit to the future <11>
Negative feedback operation of $\Delta\Sigma$ A-D converter
-
- 219** Prescription for surge suppression <measure against noise>
Impulse noise suppression
-
- 224** Learn from one's mistake <5>
Cannot dissipate heat
-
- 226** Electronics of the universe <2>
My computer
-
- 228** Learn from an expert! Efforts to start new business <2>
Kawahara - Kyou Denshi Kenkyujyo
-
- 230** Checkmate circuit <5>
Take a balance between low DC offset and frequency range

- 231** Reader's Forum **232** Information **234** Next issue/Editorial voice

CQ Publishing Co., Ltd.
1-14-2 Sugamo Toshima ward Tokyo,170-8461 JAPAN
Phone : Sales +81-3-5395-2141
Advertisement +81-3-5395-2131
Editorial +81-3-5395-2123
Postal Transfer : 00100-7-10665

Publisher : Sanae Mizoguchi
Editor-in-chief : Yuji Teramae
Copyright © 2010 by CQ Publishing Co., Ltd.
Issue : June 1st, 2010 (Monthly issued on the 1st day)
Joint to the Japan Audit Bureau of Circulations (ABC)
(Retail price is on the back cover)

Printing : Sanko Printing Co., Ltd. / Dainippon Printing Co., Ltd. /
Miwa Printing Co., Ltd. / Sankyo Graphics Co., Ltd. /
Kuni-media Co., Ltd.
Binding : Hoshino Binding Books Co., Ltd.
Printed in Japan

